

GUMET Sz. Geneja, Kozlowska, Latos Spolka Jawna 23-200 Krasnik, ul. Kolejowa 12, POLAND

Marketing and Sales Department Phone: +48 81 825-32-41 e-mail: marketing@gumet.pl

www.gumet.pl



ISO 9001:2015 ISO 14001:2015

Production of elastomer inlet pipe lip seals


At Gumet, we manufacture high-quality rubber inlet pipe lip seals designed to provide exceptional sealing and protection for pipes penetrating manhole walls. Our seals are trusted across various sectors, including telecommunications, energy networks, polyethylene (PE) water meter wells, sanitary sewers, and tanks. With a focus on durability and reliability, Gumet delivers innovative sealing solutions that ensure your systems remain secure and efficient.





Dimensions (Type):

No	Seal	Pipe outer diameter [mm]	Hole cut diameter [mm]	d _{min} [mm]	d _{max} [mm]	H [mm]
1.	Ø 32	32	37 ₍₋₁₎	25	32	22
2.	Ø 40	40	46 (-1)	35	41	25
3.	Ø 50	50	57 ₍₋₁₎	36	52	25
4.	Ø 63	63	72 (-1,5)	48	64	25
5.	Ø 75	75	86 (-1,5)	54	74	32
6.	Ø 90	90	104 (-2)	65	90	28
7.	Ø 110	110	123 ₍₋₂₎	85	110	30
8.	Ø 125	125	138 (-2)	100	127	30
9.	Ø 160	160	173 (-2)	115	163	30
10.	Ø 200	200	213 (-2)	170	202	32
11.	Ø 250	250	264 (-2)	223	250	32
12.	Ø 315	315	335 (-3)	282	317	32



Material:

EPDM, NBR

Example:

Pipe outer diameter = 32 mm; D = 37 mm; dmin = 25 mm; dmax = 32 mm; H = 22 mm;

Lip seal Ø32

Attention:

At the customer's request, we can produce rubber lip seals in other dimensions and also on other rubber blends.

Drawing inquiries are welcome